



LITHIUM 5% MOLY GREASE

EXTREME PRESSURE PERFORMANCE FROM -23°C TO 232°C!

A versatile **HEAVY DUTY** bearing grease fortified with synthetic polymers, rust and corrosion inhibitors.

It's formulated with extreme pressure agents to provide optimal lubrication and extreme pressure capability in the most severe conditions.



MEETS & EXCEEDS OEM WARRANTY REQUIREMENTS

TYPICAL PROPERTIES

NLGI Grade	2
Color	Dark Gray
Thickener	Lithium Complex
Kinematic viscosity of base oils @40°C (ASTM 445)	237.4 cSt
@ 100°C	20.4cSt
Operating temperature range	-23°C to 232°C
Penetration @ 25°C (ASTM D-1403), mm10	
Unworked	275
Worked 60 strokes	277
Worked 60,000 strokes	288
Dropping Point (ASTM D-2265)	525°F+
4-Ball Wear Test (ASTM D-2266)	
mm scar, 40kg, 1200 RPM, 24°C, 1H	0.54mm
4-Ball EP test (ASTM D-2596) LWI, kg	>75
Weld point, kg	500
Timken OK Load (ASTM D-2509) lbs/kg	55/25
Rust test (ASTM D-1743)	Pass
Copper Corrosion test (ASTM D-130)	Pass/1b
Water Washout (ASTM D-1264) @ 80°C, % loss	<2.0%
Viscosity Index (ASTM D-2270)	101
Pour Point, °C	-10°C(5)
Evaporation @260°C (Noack) % loss	4

ADVANTAGES:

- Extreme pressure protection
- Heavy load carrying capability
- Shear stability
- Displaces water & moisture
- Oxidation resistant
- Corrosion resistant
- Cling capability
- Seal compatibility
- Extreme temperature range
- Reduces downtime

ProOne#	Size	Case Pack
48014	14 oz/397g Cartridge	12
48035	35 lb./15.9 kg Pail	1
48120	120 lb./54.4 kg Keg	1
48400	400 lb./181.4 kg Drum	1



@ProOneAus1



Sales: 1800 427 5625 / (02) 9793 2511